

Euronit Profiled Sheeting Maintenance of Profiled Sheeting

TECHNICAL
NOTE
Et-01-13 en v1

Euronit fibre cement sheets and fittings are low maintenance materials.

In early life, it is advisable to check whether any settlement has occurred, and if necessary fasteners should be retightened. In later life, fixing accessories may deteriorate so should be inspected periodically and replaced as necessary.

Natural grey and Farmscape Anthracite products require no routine maintenance to achieve the design life of the material.

If maintenance painting is to be carried out on painted sheets, this should be considered after 15-20 years. The paints used should be water based acrylics.

Should there be any build up of moss on the roof which interferes with drainage, this should be removed.

If access onto the roof surface is required, use crawling boards, roof ladders or other staging to spread the load. Unless all the work and access is on staging or platforms with guard rails, safety nets should be installed under.

Disclaimer

The information in this Material Information Sheet is correct at time issuing. However, due to our committed program of continuous material and system development we reserve the right to amend or alter the information contained therein without prior notice. Please contact your local Etex Exteriors Sales Organization to ensure you have the most current version. All figures contained in this document are illustrations and should not be used as construction drawings. This information is supplied in good faith and no liability can be accepted for any loss or damage resulting from its use. This document is protected by international copyright laws. Reproduction and distribution in whole or in part without prior written permission is strictly prohibited. Euronit and logos are trademarks of Etex NV or an affiliate thereof. Any use without authorisation is strictly prohibited and may violate trademark laws.